




FILLING & CLOSING MACHINES

SEMI AUTOMATIC FILLER SAFE



From the Fischbach machinery portfolio for cartridge filling, accessorizing and case packing.

Fischbach KG
51766 Engelskirchen, Germany
Telefon: +49 2263 609 0
info@fischbach-fi.com

Fischbach Ibérica, S.A.
17410 Sils (Girona), Spain
Telefon: +34 972 168 487
spain@fischbach-fi.com

Fischbach Belgium N.V.
9140 Temse, Belgium
Telefon: +32 371 096 20
belgium@fischbach-fi.com

Fischbach USA Inc.
 Elizabethtown, Kentucky, 42701 USA
Telefon: +1 270 769 9333
usa@fischbach-fi.com

Fischbach Korea Co., Ltd.
Songpa-Gu, Seoul, Korea
Telefon: +82 2 425 3092
korea@fischbach-fi.com

Fischbach (Shanghai) Co., Ltd.
Shanghai, China 201708
Telefon: +86 21 6979 1423
china@fischbach-fi.com

Fischbach U.K. Ltd.
Cheshire WA7 1SN, Great Britain
Telefon: +44 1928 579 320
uk@fischbach-fi.com

www.fischbach-fi.com



FILLING & CLOSING MACHINES

SEMI AUTOMATIC FILLER SAFE

Semi Automatic Cartridge Filling and Plunger Setting System: A cost effective machine for up to 28 cartridges per minute.

FEATURES

- > Processes plastic, aluminium or fiber cartridges; with or without integrated nozzle.
- > Supports very short run length due to easy and quick exchangeability of all wetted parts.
- > Filling station with shuttle system for reliable filling of thin-walled or slightly oval cartridges.
- > Highly precise, pneumatically driven volume dosing system guarantees +/- 0.5g dosing accuracy per cartridge at various viscosities.
- > Optimized spinning wire material cut off facilitates plunger insertion without air pockets.
- > Plungers can be inserted with or without the support of venting wires.
- > All machine components are easily accessible for cleaning and maintenance.
- > All safety devices are in compliance with the European CE Standard.

OPTIONS

- > Automatic cartridge magazine with conveyor
- > Automatic plunger sorter/feeder

TECHNICAL DATA

Type: Cartridge Filling and Closing machine SAFE

Output: 28 cartridges per minute at 310 ml depending on the viscosity of the material filled

Dosing: Pneumatic

Dosing Range: 240 ml to 500 ml

Connecting height at Product Infeed: 1000 mm or variable through optional height adjustment

Voltage: 230 V / 400 V, 50 Hz / 60 Hz

Control: PLCP

Power Consumption:

Air Pressure: 6 bar minimum (87 psi.)

Air Consumption: 450 NL per minute at 6 bar

Weight: 270 kg



Fischbach KG
51766 Engelskirchen, Germany
Telefon: +49 2263 609 0
info@fischbach-fi.com

Fischbach Ibérica, S.A.
17410 Sils (Girona), Spain
Telefon: +34 972 168 487
spain@fischbach-fi.com

Fischbach Belgium N.V.
9140 Temse, Belgium
Telefon: +32 371 096 20
belgium@fischbach-fi.com

Fischbach USA Inc.
 Elizabethtown, Kentucky, 42701 USA
Telefon: +1 270 769 9333
usa@fischbach-fi.com

Fischbach Korea Co., Ltd.
Songpa-Gu, Seoul, Korea
Telefon: +82 2 425 3092
korea@fischbach-fi.com

Fischbach (Shanghai) Co., Ltd.
Shanghai, China 201708
Telefon: +86 21 6979 1423
china@fischbach-fi.com

Fischbach U.K. Ltd.
Cheshire WA7 1SN, Great Britain
Telefon: +44 1928 579 320
uk@fischbach-fi.com

www.fischbach-fi.com